

Product brochure

05.09.2026

KERN CKE 65K0.2

Easy to use, self-explanatory counting scale with laboratory accuracy, counting resolution 325.000 points

ENGLISH



CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

+49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com



FEATURES

- Precise, intuitive to use and digital – with our counting scales you can accelerate your annual stock taking processes and thus save time and money
- Self-explanatory, graphic control panel, the workings steps can be understood immediately, even without operating instructions
 - no learning time = reduces costs
 - ideal for untrained users
 - visualised process avoids operating errors
- The 4 steps are carried out from left to right:
 - [[1]] Place the empty container onto the weighing plate and tare by pressing the TARE key
 - [[2]] Place the reference quantity for the goods to be counted into the container (5, 10, 20 or any number of pieces)
 - [[3]] Confirm the selected reference quantity by pressing the key (5, 10, 20 or any number of pieces)
 - [[4]] Pour in the goods to be counted. The number of pieces will immediately be shown in the display
- Precise counting: The automatic reference weight optimisation of reference weight gradually improves the average piece weight value
- KERN Universal Port (KUP): permits the connection of an external KUP interface adapter, such as, for example, RS-232, USB, Bluetooth, WiFi or Ethernet, for the exchange of data and control commands, without any installation outlay
- KERN Communication Protocol (KCP): The KCP permits searching and remote control of the balance using external control devices or computers
- Two balances in one: Changes from counting mode to weighing mode at the touch of a key
- Protective working cover included with delivery

TECHNICAL DATA

- Large backlit LCD display, digit height 25 mm
- Dimensions weighing surface, stainless steel, W×D 340×240 mm
- Overall dimensions 350×390×120 mm
- Net weight approx. 7 kg
- Permissible ambient temperature -10 °C/40 °C

MAIN SCOPE OF APPLICATIONS

- Industrial applications
- Series production
- Production monitoring
- Quality control
- Counting applications
- Order picking and inventory

PICTOGRAMS

Standard



Option



MODEL OVERVIEW

Model	Weighing capacity [Max]	Readability [d]	Smallest part weight (Normal)	Counting resolution Points	Dimensions weighing surface
CKE 8K0.05	8 kg	0,00005 kg	500 mg	160.000	340×240 mm
CKE 16K0.1	16 kg	0,0001 kg	1 g	160.000	340×240 mm
CKE 16K0.05	16 kg	0,00005 kg	500 mg	320.000	340×240 mm
CKE 36K0.1	36 kg	0,0001 kg	1 g	360.000	340×240 mm
CKE 65K0.2	65 kg	0,0002 kg	2 g	325.000	340×240 mm
CKE 360-3	360 g	0,001 g	20 mg	180.000	82 mm
CKE 3600-2	3600 g	0,01 g	200 mg	180.000	130×130 mm
CKE 6K0.02	6000 g	0,02 g	200 mg	300.000	340×240 mm

ACCESSORIES

Model	Description
CFS-A03	Signal lamp KERN CFS-A03
FKB-A02	Protective working cover FKB-A02
FKB-A02S05	Protective working cover FKB-A02S05, scope of delivery: 5 items

Model	Description
KUP-01	RS-232 interface KUP-01
KUP-03	Interface USB-Device KUP-03-2026e
KUP-04	Ethernet interface KUP-04
KUP-05	WiFi interface KUP-05
KUP-06	Bluetooth BLE interface KUP-06
KUP-13	Extension box KUP-13
YKA-27	Power adapter YKA-27 (5,9V, 1A 100 V - 240 V, 50 / 60 Hz EURO, UK, US, CH)
YKG-01	Dot Matrix Printer YKG-01
YKH-01	Thermal printer YKH-01
YKR-01	Rechargeable battery pack YKR-01
YKT-01	Needle printer YKT-01

SOFTWARE

Model	Description
SCD-4.0-DL	Software SCD-4.0-DL (Scope of supplies: Download link for 1 license)
SCD-4.0-DLS05	Software SCD-4.0-DLS05 (Scope of supplies: Download link for 5 licenses)
SCD-4.0-PRO-DL	Software SCD-4.0-PRO-DL (Scope of supplies: Download link for 1 license)
SCD-4.0-PRO-DL-AS05	Software SCD-4.0-PRO-DL-AS05 (Scope of supplies: Download link for 5 licenses)
SET-01	Software KERN EasyTouch SET-01-2025a Base
SET-01	Software KERN EasyTouch SET-01 Base
SET-04	Software KERN EasyTouch SET-04-2025a Density
SET-04	Software KERN EasyTouch SET-04 Density
SET-05	Software KERN EasyTouch SET-05-2025a Dynamic
SET-05	Software KERN EasyTouch SET-05 Dynamic
SET-06	Software KERN EasyTouch SET-06-2025a Classification
SET-06	Software KERN EasyTouch SET-06 Classification
SET-07	Software KERN EasyTouch SET-07-2025a Variable
SET-07	Software KERN EasyTouch SET-07 Variable
SET-08	Software KERN EasyTouch SET-08-2025a Take-out
SET-08	Software KERN EasyTouch SET-08 Take-out
SET-10	Software KERN EasyTouch SET-10 Save Server

Model	Description
SET-11	Software KERN EasyTouch SET-11-2025a Safety
SET-11	Software KERN EasyTouch SET-11 Safety
SET-14	Software KERN EasyTouch SET-14-2025a Individual Print
SET-14	Software KERN EasyTouch SET-14 Individual Print
SET-16	Software KERN EasyTouch SET-16-2025a Batch and Statistics
SET-16	Software KERN EasyTouch SET-16 Batch and Statistics
SET-17	Software KERN EasyTouch SET-17-2025a PrePack
SET-17	Software KERN EasyTouch SET-17 PrePack
SET-18	Software KERN EasyTouch SET-18-2025a Container Master
SET-18	Software KERN EasyTouch SET-18 Container Master
SET-21	Software KERN EasyTouch SET-21-2025a Formulation
SET-21	Software KERN EasyTouch SET-21 Formulation
SET-22	Software KERN EasyTouch SET-22-2025a Difference
SET-22	Software KERN EasyTouch SET-22 Difference
SET-31	Software KERN EasyTouch SET-31-2025a Tolerance
SET-31	Software KERN EasyTouch SET-31 Tolerance
SET-32	Software KERN EasyTouch SET-32-2025a Count
SET-32	Software KERN EasyTouch SET-32 Count
SET-33	Software KERN EasyTouch SET-33-2025a Target Count
SET-33	Software KERN EasyTouch SET-33 Target Count
SET-35	Software KERN EasyTouch SET-35-2025a Assembly Count
SET-35	Software KERN EasyTouch SET-35 Assembly Count
SET-37	Software KERN EasyTouch SET-37-2025a Export Manager
SET-37	Software KERN EasyTouch SET-37 Export Manager
SET-39	Software KERN EasyTouch SET-39 Data Interface
SET-40	Software KERN EasyTouch SET-40 Protect
SET-46	Software KERN EasyTouch SET-46-2025a Backup Scheduler
SET-46	Software KERN EasyTouch SET-46 Backup Scheduler
SET-51	Software KERN EasyTouch SET-51-2025a Audit Logs
SET-51	Software KERN EasyTouch SET-51 Audit Logs
SET-52	Software KERN EasyTouch SET-52-2025a Inventory

Model	Description
SET-52	Software KERN EasyTouch SET-52 Inventory
SET-261	Software KERN EasyTouch SET-261 Audio Management
SET-311	Software KERN EasyTouch SET-311-2025a Quick Key
SET-311	Software KERN EasyTouch SET-311 Quick Key
SET-411	Software KERN EasyTouch SET-411-2025a Hotkeys
SET-411	Software KERN EasyTouch SET-411 Hotkeys

SERVICES

Model	Description
963-129	DAkkS calibration certificate 963-129
969-517	Confirmation of the manufacturer's specification (only in combination with DAkkS calibration certificate)969-517
970-101	Warranty extension (+2 years) 970-101

KERN Pictogram Overview

	External adjustment: Adjusting accuracy using external adjustment weight
	KERN IoT-Line balances – smart weighing solutions for the digital future
	KERN Universal Port (KUP): allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, USB, Bluetooth, WiFi, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort
	KERN Communication Protocol (KCP): a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems
	Piece counting: Reference quantities selectable. Display can be switched from piece to weight
	Measuring with tolerance range (checkweighing): Upper and lower limit values can be programmed, e.g. for sorting, portioning or for measuring coatings or material thicknesses. The process is supported by an acoustic and/or optical signal
	Suspended weighing: Load support with hook on the underside of the balance
	Battery operation: Ready for battery operation
	Universal plug-in power supply: With universal input and optional input socket adapters for EU, CH, GB or EU, CH, GB, US or EU, CH, GB, US, AUS
	Weighing principle Strain gauges: Electrical resistor on an elastic deforming body
	Package shipment by courier service: The duration of internal product provision is one day
	EasyTouch: Suitable for the connection, data transmission and control through PC or tablet
	Data interface RS-232: For connection to printers, PCs or other peripheral devices for data transfer over longer distances. Network in bus topology possible
	Data Interface USB: For connection to printers, PCs or other peripheral devices
	Data interface WiFi: For data transfer to printers, PCs or other peripheral devices
	Data interface Bluetooth: For connection to printers, PCs or other peripheral devices
	Network interface: For connecting the measuring device to an Ethernet network
	Rechargeable battery pack: Rechargeable set
	Accredited calibration (DKD): The duration of the accredited calibration is 3 working days